



skandia

CELEBRATING
30
years
of service

Skandia Antennas Pty Ltd
A.B.N. 49 130 441 548
131 Wedgewood Road
Hallam VIC 3803
PHONE: 03 8786 3080
EMAIL: orders@skandia.com.au
WEB: www.skandia.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** FVK12402
- 2. DESCRIPTION** 24/0.2 (0.75mmsq) Tinned Annealed Copper
V90HT PVC Insulated
0.6/1KV rated to AS/NZS3191
Oxygen Free copper. RoHS Compliant.
- 3.1 CONDUCTOR:** 24 strands of 0.20mm nom. Tinned Annealed Copper to AS/NZS1125, drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C: 26.7 ohms / km
- 3.2 INSULATION:** Coloured P.V.C. type V90HT to AS/NZS3808 (Formerly V105)
Nominal Diameter: 2.8 mm
Nominal Wall Thickness: 0.8 mm
- 3.3 IDENTIFICATION:** Indented into the insulation at max. 200mm:
TYCAB HT90 0.6/1KV
- 3.4 EARTH STRIPE:** Green with Yellow extruded stripe, the stripe surface coverage greater than 30% and less than 70% coverage, as per AS/NZS3191. Applied as a dual stripe.



Note: Specification subject to change without prior notice

AUSTRALIAN MADE CABLES LEADING THE WAY